



www.onelitepharma.com



AR2 VERTICAL

Equipment

It is equipped with a PLC touchscreen 7"; it has a memory capacity for 40 labelling programs. It can operate as a self-standing unit or it can be installed onto new labelling machines as well as onto those that are already in use.

Optional

- Stainless tripod stand.
- Micro mechanical transparent label detector.
- Hot Stamping Encoder.

AR2 Automatic labeler head

AR2 is an automatic labeler head for applying self-adhesive labels, powered by stepper motor or servomotor and controlled by microprocessor.

It can place labels in different positions: the side, the front, the top and the bottom. It allows adapting a **hot stamping machine** as well as an encoder and offers an accuracy of +/- 0.5 mm.



AR2 HORIZONTAL

Various applications

- Easy access crankcase and traction roller set with “Click-Clack” closing system.
- Variable position applicator reinforced with rollers assembled on bearings.
- It can place labels in different positions.



Available in the following versions:

1) **Maximum label width:**

▪ **AR2-80 for 80 mm**

▪ **AR2-130 for 130 mm**

▪ **AR2-200 for 200 mm**

2) Right or left handed.

3) **Maximum speed:**

Mod. 20, 20 m/min; Mod. 30, 30 m/min; Mod. 50, 50 m/min; Mod. 80, 80 m/min.

Technical Characteristics AR2

MODEL	STEP BY STEP
Supply (V)	220 V (50 Hz)
Weight (Kg)	50-60
Max. speed (m/min)	20/30/50/80
Max. diam. Reel	300 mm
Max. width Label	80/130/200 mm
Min. Label size	15 x 15 mm
Power (W)	200